



Standard Features:

- Double deflection adjustable blade grille
- Front blades are parallel to shortest dimension
- Back blades are parallel to longest dimension
- Allows for 4-way airflow adjustment
- Galvanized steel construction
- Nylon bushings on adjustable blades allow for easy adjustment and prevents metal on metal rattle for quiet operation
- High quality foam gasketing for tight seal with duct
- Product sizes available to fit spiral pipe sizes 6" – 48"
- Galvanized Finish

Options:

- Adjustable airfoil blades (A-USR34)
- Perforated face grille (USR-PERF)
- Recessed screwdriver operated Opposed Blade Damper (USR34-0)
- Half-length screwdriver operated Scoop Extractor (USR34-SC)
- Full-length screwdriver operated Scoop Extractor (20" max length scoop) (USR34-FS)

Finishes:

STANDARD COLORS

- Soft White
- Driftwood Tan
- Galvanized

DESIGNER COLORS

- Black
- Bronze
- Storm Gray
- Cement Gray

- Aluminum Paint
- Coffee Tan
- Warm White
- Glossy White

Chart denotes spiral pipe diameter range compatible with product size. Example: USR34-10x3 fits pipe sizes 6" through 24" diameter.

USR34 Series Spiral Pipe Sizing Chart

SIZES OFFERED	PRODUCT WIDTH								
	10	12	14	16	18	20	24	30	36
PRODUCT HEIGHT									
3	6" – 24" dia.	6" – 24" dia.	6" – 24" dia.	6" – 24" dia.	6" – 24" dia.	6" – 24" dia.	6" – 24" dia.	6" – 24" dia.	6" – 24" dia.
4	10" – 24" dia.	10" – 24" dia.	10" – 24" dia.	10" – 24" dia.	10" – 24" dia.	10" – 24" dia.	10" – 24" dia.	10" – 24" dia.	10" – 24" dia.
6	12" – 24" dia.	12" – 24" dia.	12" – 24" dia.	12" – 24" dia.	12" – 24" dia.	12" – 24" dia.	12" – 24" dia.	12" – 24" dia.	12" – 24" dia.
8	n/a	20" – 36" dia.	20" – 36" dia.	20" – 36" dia.	20" – 36" dia.	20" – 36" dia.	20" – 36" dia.	20" – 36" dia.	20" – 36" dia.
10	n/a	n/a	n/a	n/a	30" – 48" dia.	30" – 48" dia.	30" – 48" dia.	30" – 48" dia.	30" – 48" dia.
12	n/a	n/a	n/a	n/a	42" – 48" dia.	42" – 48" dia.	42" – 48" dia.	42" – 48" dia.	42" – 48" dia.

Additional Information:

Submittal Notes

Project / Location:	
Engineer:	
Architect:	
Contractor:	