

Performance Data



DVD Series 3-way

		FPM	300	400	500	600	700	800	900	1000	1100																	
		VP	0.006	0.01	0.016	0.022	0.031	0.04	0.05	0.062	0.075																	
6x6 .212ft/sq	CFM	64	85	106	127	148	170	191	212	233																		
	SP	0.011	0.011	0.011	0.022	0.027	0.032	0.043	0.065	0.086																		
	TP	0.017	0.021	0.027	0.044	0.058	0.072	0.093	0.127	0.161																		
	NC	-	-	-	16	22	27	30	32	35																		
	3w throw	4	5	10	5	6	13	5	9	15	6	10	16	8	11	18	9	14	19	10	14	20	11	15	22	13	16	24
	FPM	300	400	500	600	700	800	900	1000	1100																		
8x8 .363ft/sq	CFM	109	145	182	218	254	290	327	363	399																		
	SP	0.011	0.011	0.022	0.022	0.032	0.043	0.054	0.076	0.097																		
	TP	0.017	0.021	0.038	0.044	0.063	0.083	0.104	0.138	0.172																		
	NC	-	-	16	16	22	32	35	37	38																		
	3w throw	4	6	11	6	7	14	6	10	17	7	11	18	8	12	19	10	15	21	11	15	22	12	17	23	14	18	26
	FPM	300	400	500	600	700	800	900	1000	1100																		
10x10 .59ft/sq	CFM	177	236	295	354	413	472	531	590	649																		
	SP	0.011	0.011	0.022	0.027	0.038	0.049	0.065	0.086	0.108																		
	TP	0.017	0.021	0.038	0.049	0.069	0.089	0.115	0.148	0.183																		
	NC	-	-	16	16	23	32	36	39	41																		
	3w throw	6	8	17	8	11	20	9	14	23	11	17	25	13	19	27	15	21	29	17	21	30	18	23	32	20	25	36
	FPM	300	400	500	600	700	800	900	1000	1100																		
12x12 .79ft/sq	CFM	237	316	395	474	553	632	711	790	869																		
	SP	0.011	0.011	0.022	0.032	0.043	0.054	0.076	0.097	0.119																		
	TP	0.017	0.021	0.038	0.054	0.074	0.094	0.126	0.159	0.194																		
	NC	-	-	16	17	24	32	37	41	44																		
	3w throw	7	11	23	10	15	26	12	19	29	15	23	32	18	25	34	21	26	37	22	28	39	23	29	41	26	32	45
	FPM	300	400	500	600	700	800	900	1000	1100																		
14x14 1.16ft/sq	CFM	348	464	580	696	812	928	1044	1160	1276																		
	SP	0.011	0.022	0.032	0.043	0.059	0.076	0.092	0.108	0.135																		
	TP	0.017	0.032	0.048	0.065	0.090	0.116	0.142	0.170	0.210																		
	NC	-	16	18	21	26	33	37	41	44																		
	3w throw	8	12	24	11	17	28	14	21	31	17	25	34	19	26	37	22	28	39	23	29	41	25	31	43	28	34	49

Performance Data



DVD Series 3-way

16x16 1.42ft/sq	FPM	300	400	500	600	700	800	900	1000	1100																	
	CFM	426	568	710	852	994	1136	1278	1420	1562																	
	SP	0.022	0.032	0.043	0.054	0.076	0.086	0.103	0.119	0.151																	
	TP	0.028	0.042	0.059	0.076	0.107	0.126	0.153	0.181	0.226																	
	NC	15	15	21	24	29	36	39	42	46																	
	3w throw	10	14	25	12	18	29	15	22	33	18	26	36	21	28	39	23	29	41	25	30	43	26	33	45	29	36
18x18 1.91ft/sq	FPM	300	400	500	600	700	800	900	1000	1100																	
	CFM	573	764	955	1146	1337	1528	1719	1910	2101																	
	SP	0.025	0.037	0.050	0.062	0.087	0.099	0.118	0.137	0.174																	
	TP	0.031	0.047	0.066	0.084	0.118	0.139	0.168	0.199	0.249																	
	NC	15	19	24	27	32	39	42	45	50																	
	3w throw	11	15	27	14	20	32	17	24	36	20	29	39	23	30	42	26	32	45	27	33	47	29	36	50	32	39
20x20 2.3ft/sq	FPM	300	400	500	600	700	800	900	1000	1100																	
	CFM	690	920	1150	1380	1610	1840	2070	2300	2530																	
	SP	0.027	0.040	0.054	0.067	0.094	0.107	0.127	0.148	0.188																	
	TP	0.033	0.050	0.070	0.089	0.125	0.147	0.177	0.210	0.263																	
	NC	16	20	26	29	33	41	45	48	50																	
	3w throw	11	16	29	14	21	34	18	26	39	21	31	42	24	32	45	27	34	48	29	35	50	31	39	53	34	42
24x24 3.30ft/sq	FPM	300	400	500	600	700	800	900	1000	1100																	
	CFM	990	1320	1650	1980	2310	2640	2970	3300	3630																	
	SP	0.029	0.043	0.058	0.072	0.101	0.116	0.138	0.159	0.203																	
	TP	0.035	0.053	0.074	0.094	0.132	0.156	0.188	0.221	0.278																	
	NC	17	21	27	31	35	44	47	50	50+																	
	3w throw	12	17	31	15	22	36	19	27	41	22	32	44	26	34	48	29	36	51	31	37	53	32	41	56	36	44

Performance Notes

- 1) Throw values are measured in feet for terminal velocities of 150/100/50 FPM
- 2) Throw data is based on supply air and room air both at isothermal conditions
- 3) Effective core areas listed in the chart are defined as the measurement of space between the blades actually being utilized by the air
- 4) Data obtained from tests conducted in accordance with ANSI/ASHRAE standard 70-2006